

TECHNICAL DATA
DATA SHEET NUMBER 583, REV. -

QUADRUPLE HALF-H DRIVER

FEATURES:

- 600 mA Output Current Capability, Per Driver
- Pulsed Current 1.2 A Per Driver
- Output Clamp Diodes for Inductive Transient Suppression
- Wide Supply Voltage Range; 4.5V to 36V
- Functional Replacement for SGS L293D

MAXIMUM RATINGS ALL RATINGS ARE OVER A FREE-AIR TEMPERATURE RANGE, UNLESS OTHERWISE SPECIFIED.

RATING	MAX.	UNITS
Logic Supply Voltage Range, V_{CC1} (see Note 1)	36	V
Output Supply Voltage Range, V_{CC2}	36	V
Input Voltage Range, V_I	7.0	V
Output Voltage Range, V_O	-3.0 to $V_{CC2}+3.0$	V
Peak Output Current (non-repetitive, $t \leq 100 \mu s$)	± 1.2	A
Continuous Output Current, I_O	± 600	mA
Continuous Total Dissipation at (or below) 25° C Free Air Temperature (2, 3)	2075	mW
Continuous Total Dissipation at 80° C Case Temperature (3)	5000	mW
Operating Case or Virtual Junction Temperature Range, T_J	-40 to +150	°C
Storage Temperature Range, T_{stg}	-65 to +150	°C
Lead Temperature 1.6 mm (1/16 inch) From Case for 10 Seconds	260	°C

- Notes:**
- 1- All voltage values are with respect to the network ground terminal.
 - 2- For operation above 25°C free air temperature, derate linearly at the rate of 16.6mW/°C.
 - 3- For operation above 25°C case temperature, derate linearly at the rate of 71.4mW/°C. Due to variations in individual device electrical characteristics and thermal resistance, the built in thermal overload protection may be activated at power levels slightly above or below the rated dissipation.

RECOMMENDED OPERATING CONDITIONS

	MIN.	MAX.	UNIT
Logic Supply Voltage, V_{CC1}	4.5	7.0	V
Output Supply Voltage, V_{CC2}	V_{CC1}	36	V
High Level Input Voltage, V_{IH}	$V_{CC1} \leq 7.0V$ $V_{CC1} \geq 7.0V$	2.3 7.0	V_{CC1} V
Low Level Input Voltage, V_{IL}	-0.3*	1.5	V
Operating Free Air Temperature, T_A	0	70	°C

*The algebraic conversion, in which the least positive (most negative) value is designated minimum, is used in this data sheet for logic voltage levels.

SENSITRON

DATA SHEET NUMBER 583, REV. -

ELECTRICAL CHARACTERISTICS

$V_{CC1} = 5V, V_{CC2} = 24V, T_A = 25^{\circ}C$

CHARACTERISTIC		CONDITIONS	MIN.	TYP.	MAX.	UNITS
High level Output Voltage (V_{OH})		$I_{OH} = -0.6A$	$V_{CC2}-1.8$	$V_{CC2}-1.4$	-	V
Low level Output Voltage (V_{OL})		$I_{OL} = -0.6A$	-	1.2	1.8	V
High level Output Clamp Voltage (V_{OKH})		$I_{OK} = -0.6A$	-	$V_{CC2}+1.3$	-	V
Low level Output Clamp Voltage (V_{OKL})		$I_{OK} = -0.6A$	-	1.3	-	V
High Level Input Current (I_{IH})	A	$V_I = 7.0V$	-	0.2	100	μA
	EN			0.2	± 10	
Low Level Input Current (I_{II})	A	$V_I = 0V$	-	-3	-10	μA
	EN			-2	-100	
Logic Supply Current (I_{CC1})	$I_O = 0A$	All outputs @ High Level		13	22	mA
		All outputs @ Low Level	-	35	60	
		All outputs @ High Imped.		8.0	24	
Output Supply Current (I_{CC2})	$I_O = 0A$	All outputs @ High Level		14	24	mA
		All outputs @ Low Level	-	2.0	6.0	
		All outputs @ High Imped.		2.0	4.0	

SWITCHING CHARACTERISTICS

$V_{CC1} = 5V, V_{CC2} = 24V, T_A = 25^{\circ}C$

CHARACTERISTIC	CONDITION	MIN.	TYP.	MAX.	UNIT
Propagation Delay Time, L-H Level Output from. A Input (t_{PLH})	$C_L = 30 pF$	-	800	-	ns
Propagation Delay Time, H-L Level Output from. A Input (t_{PHL})		-	400	-	ns
Transition Time, L-H Level Output (t_{TLH})		-	300	-	ns
Transition Time, H-L Level Output (t_{THL})		-	300	-	ns

TECHNICAL DATA

DISCLAIMER:

1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the Sensitron Semiconductor sales department for the latest version of the datasheet(s).

2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.

3- In no event shall Sensitron Semiconductor be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). Sensitron Semiconductor assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.

4- In no event shall Sensitron Semiconductor be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.

5- No license is granted by the datasheet(s) under any patents or other rights of any third party or Sensitron Semiconductor.

6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of Sensitron Semiconductor.

7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.